

## PEDJ



## Fire fighting system

Model	Power Electric		Perform		Voltage V	Power Diesel hp	Diesel rpm	Power Jockey hp
	kW	hp	Q GPM	H bar				
50/6-5.5-5.5-2	4	5.5	50	6	380	5.5	3000	2
80/7-10-8.6-3	7.5	10	80	7	380	8.6	3000	3
100/7-10-8.6-3	7.5	10	100	7	380	8.6	3000	3
120/7-10-10-3	7.5	10	120	7	380	10	3000	3
150/7-15-10-3	11	15	150	7	380	10	3000	3
200/7-20-27-3	15	20	200	7	380	27	3000	3
250/7-25-27-4	18.5	25	250	7	380	27	3000	4
300/7-30-32-4	22	30	300	7	380	32	3000	4
350/7-30-32-4	22	30	350	7	380	32	3000	4
400/7-40-38-5.5	30	40	400	7	380	38	3000	5.5
500/8-50-58-5.5	37	50	500	8	380	58	3000	5.5
750/8-75-75-7.5	55	75	750	8	380	75	3000	7.5
1000/8-100-99-10	75	100	1000	8	380	99	3000	10
1250/8-150-130-10	110	150	1250	8	380	130	3000	10
500/10-60-61-7.5	45	60	500	13	380	61	3000	7.5
750/10-100-99-10	75	100	750	13	380	99	3000	10
1000/10-125-113-12	90	125	1000	13	380	113	3000	12
1250/10-180-170-15	132	180	1250	13	380	170	3000	15
500/13-100-99-12	75	100	500	13	380	99	3000	12
750/13-125-113-12	90	125	750	13	380	113	3000	12
1000/13-150-130-15	110	150	1000	13	380	130	3000	15
1250/13-220-170-15	160	220	1250	13	380	170	3000	15
1500/13-220-170-15	160	220	1500	13	380	170	3000	15

Design	With <b>Electric-Diesel-Jockey</b> design
Including	Control panel board, Manifold suction pipe, Discharge pipe with gate valves, check valves, flexible expansion anti-vibration, Pressure switches, Pressure gauge, Base frame mounted.
Optional	Other sizes can provide on request

## PEDJ



## Fire fighting system

Model	Power Electric		Perform		Voltage V	Power Diesel hp	Diesel rpm	Power Jockey hp
	kW	hp	Q GPM	H bar				
50/6-5.5-5.5-2	4	5.5	50	6	220/380	5.5	3000	2
80/7-10-8.6-2	7.5	10	80	7	220/380	8.6	3000	2
100/7-10-8.6-3	7.5	10	100	7	220/380	8.6	3000	3
120/7-10-10-3	7.5	10	120	7	220/380	10	3000	3
150/7-15-10-3	11	15	150	7	220/380	10	3000	3
200/7-20-27-3	15	20	200	7	220/380	27	3000	3
250/7-25-27-3	18.5	25	250	7	220/380	27	3000	3
300/7-30-32-4	22	30	300	7	220/380	32	3000	4
350/7-30-32-4	22	30	350	7	220/380	32	3000	4
400/7-40-38-5.5	30	40	400	7	220/380	38	3000	5.5
500/8-50-58-5.5	37	50	500	8	220/380	58	3000	5.5
750/8-75-75-7.5	55	75	750	8	220/380	75	3000	7.5

<b>1000/8-100-99-10</b>	75	100	1000	8	220/380	99	3000	10
<b>1250/8-150-130-10</b>	110	150	1250	8	220/380	130	3000	10
<b>500/10-60-61-7.5</b>	45	60	500	13	220/380	61	3000	7.5
<b>750/10-100-99-10</b>	75	100	750	13	220/380	99	3000	10
<b>1000/10-125-113-12</b>	90	125	1000	13	220/380	113	3000	12
<b>1250/10-180-170-15</b>	132	180	1250	13	220/380	170	3000	15
<b>500/13-100-99-10</b>	75	100	500	13	220/380	99	3000	10
<b>750/13-125-113-12</b>	90	125	750	13	220/380	113	3000	12
<b>1000/13-150-130-15</b>	110	150	1000	13	220/380	130	3000	15
<b>1250/13-220-170-15</b>	160	220	1250	13	220/380	170	3000	15
<b>1500/13-220-170-15</b>	160	220	1500	13	220/380	170	3000	15

Design	With <b>Electric-Diesel-Jockey</b> design
Including	Control panel board, Manifold suction pipe, Discharge pipe with gate valves, check valves, flexible expansion anti-vibration, Pressure switches, Pressure gauge, Base frame mounted.
Optional	Other sizes can provide on request