

PV

Multi-Stage Jockey pump

Model	Power		Perform		Ports mm	Impeller	Wt kg	Dim cbm
	kw	hp	Qm m³/h	Hm m				
PV 4×7/1.5	1.1	1.5	7.2	60.7	25×25	PPO	27	0.044
PV 4×9/2	1.5	2	7.2	78	25×25	PPO	32	0.048
PV 4×13/3	2.2	3	7.2	113	25×25	PPO	37	0.056
PV 4×16/4	3	4	7.2	139	25×25	PPO	47	0.071
PV 6×5/1.5	1.1	1.5	9.6	44.4	32×32	PPO	25	0.039
PV 6×8/2	1.5	2	9.6	71.1	32×32	PPO	30	0.046
PV 6×11/3	2.2	3	9.6	97.7	32×32	PPO	35	0.052
PV 6×15/4	3	4	9.6	133	32×32	PPO	45	0.068
PV 8×4/1.5	1.1	1.5	13.2	36.8	40×40	PPO	25	0.037
PV 8×7/2	1.5	2	13.2	64.4	40×40	PPO	30	0.044
PV 8×9/3	2.2	3	13.2	82.8	40×40	PPO	35	0.048
PV 8×12/4	3	4	13.2	110	40×40	PPO	45	0.062
PV 8×16/5.5	4	5.5	13.2	147	40×40	PPO	50	0.071
PV 12×3/1.5	1.1	1.5	18	31	50×50	PPO	24	0.035
PV 12×5/2	1.5	2	18	51.7	50×50	PPO	29	0.039
PV 12×7/3	2.2	3	18	72.3	50×50	PPO	34	0.044
PV 12×9/4	3	4	18	93	50×50	PPO	44	0.055
PV 12×12/5.5	4	5.5	18	122	50×50	PPO	50	0.062
PV 12×17/7.5	5.5	7.5	18	176	50×50	PPO	60	0.079
PV 30×7/10	7.5	10	45	104	65×65	PPO	86	0.100
PV 30×9/12	9.2	12.5	45	133	65×65	PPO	92	0.110
PV 30×11/15	11	15	45	163	65×65	PPO	100	0.119

Pump Case	Anti-corrosive coating cast iron
Shaft	Chrome Plating Steel
Seal	Mechanical Seal, Carbon-SiC-NBR
Bearing	NSK
Flange	Suction and discharge port in G20 thread
Motor	Insulation class F, Protection IP 55

PV

Multi-Stage Jockey pump

Model	Power		Perform		Ports mm	Impeller	Wt kg	Dim cbm
	kw	hp	Qm m³/h	Hm m				
PV 4×4/1.5	1.1	1.5	7.2	52	25×25	PPO	26	0.042
PV 4×6/2	1.5	2	7.2	77	25×25	PPO	31	0.047
PV 4×8/3	2.2	3	7.2	104	25×25	PPO	36	0.051
PV 4×10/4	3	4	7.2	129	25×25	PPO	46	0.059
PV 4×13/5.5	4	5.5	7.2	168	25×25	PPO	51	0.066
PV 4×16/7.5	5.5	7.5	7.2	206	25×25	PPO	61	0.076
PV 6×3/1.5	1.1	1.5	9.6	40	32×32	PPO	25	0.040
PV 6×5/2	1.5	2	9.6	66	32×32	PPO	30	0.044
PV 6×7/3	2.2	3	9.6	92	32×32	PPO	35	0.049
PV 6×9/4	3	4	9.6	119	32×32	PPO	45	0.057
PV 6×12/5.5	4	5.5	9.6	159	32×32	PPO	50	0.064
PV 6×16/7.5	5.5	7.5	9.6	211	32×32	PPO	60	0.076
PV 8×4/2	1.5	2	13.2	53	40×40	PPO	29	0.042

PV 8×6/3	2.2	3	13.2	79	40×40	PPO	34	0.047
PV 8×8/4	3	4	13.2	105	40×40	PPO	44	0.054
PV 8×10/5.5	4	5.5	13.2	132	40×40	PPO	49	0.059
PV 8×13/7.5	5.5	7.5	13.2	171	40×40	PPO	59	0.069
PV 8×17/10	7.5	10	13.2	224	40×40	PPO	64	0.078
PV 12×3/2	1.5	2	18	44	50×50	PPO	27	0.040
PV 12×4/3	2.2	3	18	59	50×50	PPO	32	0.042
PV 12×5/4	3	4	18	73	50×50	PPO	40	0.047
PV 12×7/5.5	4	5.5	18	102	50×50	PPO	45	0.052
PV 12×9/7.5	5.5	7.5	18	132	50×50	PPO	55	0.060
PV 12×11/10	7.5	10	18	161	50×50	PPO	62	0.065
PV 12×15/15	11	15	18	220	50×50	PPO	80	0.104
PV 30×5/10	7.5	10	45	105	65×65	PPO	84	0.086
PV 30×6/12	9.2	12.5	45	126	65×65	PPO	90	0.091
PV 30×8/15	11	15	45	168	65×65	PPO	97	0.100

Pump Case	Anti-corrosive coating cast iron
Shaft	Chrome Plating Steel
Seal	Mechanical Seal, Carbon-SiC-NBR
Bearing	NSK
Flange	Suction and discharge port in G20 thread
Motor	Insulation class F, Protection IP 55